

1                                    TITLE OF THE INVENTION

2            **Method and System for Connecting a Mobile Communication Unit**  
3                                    **to a Personal Computer**

4                                    BACKGROUND OF THE INVENTION

5                                    Field of the Invention

6            The present invention relates generally to personal computers, and  
7            more specifically to a method and a system for connecting a mobile unit to a  
8            computer.

9                                    Description of the Related Prior Art

10           It is known to use a connection device for coupling a cellular mobile  
11           telephone to a personal computer to provide data communication via a  
12           mobile network. A known connection device as disclosed in Japanese Patent  
13           Publication 97-162960 is comprised of an AC-DC converter battery charger  
14           for charging the battery of the mobile unit with energy obtained from a  
15           commercial AC outlet. However, due to the use of AC-DC converter battery  
16           charger, a commercial AC outlet must be available at a suitable location and a  
17           power supply code must be attached to the connection device for receiving  
18           AC energy from the power outlet. Another connection device disclosed in  
19           Japanese Patent Publication 98-285254 includes a first power connector for  
20           exclusively for use in charging the battery of a mobile unit and a second  
21           power connector exclusively for use in operating the mobile unit. These  
22           power connectors are provided separately from a data connector that is used  
23           to transport data between the mobile unit and a personal computer. While  
24           the use of two power connectors allows the mobile unit to proceed  
25           communication with the mobile network while its battery is being charged, a

1 power supply code is still required to receive energy from an external power  
2 source.

### 3 SUMMARY OF THE INVENTION

4 It is therefore an object of the present invention to relieve the user of a  
5 computer and a mobile communication unit from the need to find a  
6 commercial AC output or a separate external power source and the need to  
7 use a power supply code for feeding the mobile unit.

8 According to a first aspect of the present invention, there is provided a  
9 method of connecting a mobile communication unit to a computer,  
10 comprising the steps of establishing a plurality of connections between  
11 internal circuitry of the mobile communication unit having a rechargeable  
12 battery and internal circuitry of a computer through a plurality of connector  
13 ports, supplying power from a power source of the computer to the  
14 rechargeable battery of the mobile communication unit, and controlling the  
15 mobile communication unit through one of the connections according to a  
16 command signal supplied to the computer.

17 According to a second aspect, the present invention provides a system  
18 for connecting a mobile communication unit to a computer. The system  
19 comprises connector having a recess for holding the mobile communication  
20 unit and a plurality of connector ports, switching circuitry for selectively  
21 establishing a connection between the internal circuitry of the computer and  
22 the internal circuitry of the mobile communication unit through the connector  
23 ports, power supply circuitry for supplying power from a power source of  
24 the computer to a rechargeable battery of the mobile communication unit,  
25 and control circuitry for controlling the mobile communication unit through

1 the established connection according to a command signal entered to the  
2 computer.

3 According to a third aspect, the present invention provides a  
4 connection device for establishing connections between a computer and a  
5 mobile communication unit having a rechargeable battery. The connection  
6 device comprises a connector having a recess for holding the mobile  
7 communication unit and a plurality of connector ports, and an interface card  
8 connected through the connector ports to the internal circuitry of the mobile  
9 communication unit and connected through a serial port to the internal  
10 circuitry of the computer. The interface card includes power supply circuitry  
11 for supplying power from a power source of the computer to the  
12 rechargeable battery of the mobile communication unit, switching circuitry  
13 for selectively establishing a connection between the internal circuitry of the  
14 computer and the internal circuitry of the mobile communication unit  
15 through the connector ports, and control circuitry for controlling the mobile  
16 communication unit through the connection according to a command signal  
17 entered to the computer.

#### 18 BRIEF DESCRIPTION OF THE DRAWINGS

19 The present invention will be described in detail further with reference  
20 to the following drawings, in which:

21 Fig. 1 is a perspective view of a notebook computer and a connector  
22 for coupling a mobile unit to the computer according to the present  
23 invention;

24 Fig. 2 is a block diagram of a personal computer and an interface card  
25 according to the present invention;

Fig. 3 is a block diagram of a mobile unit according to the present invention;

Fig. 4 is a perspective view of a computer screen on which a simulated image of the mobile unit is displayed; and

Fig. 5 is a perspective view of a connector in which the interface card of the present invention is installed.

#### DETAILED DESCRIPTION

Referring to Fig. 1, there is shown a personal computer and a connector 4 for coupling a mobile communication unit 5 to the computer 1 and for operating the mobile unit 5 from the computer 1 according to the present invention. For the purpose of disclosure, the computer 1 is shown and described as a notebook computer having a keyboard 2 incorporated as an integral part of the computer. A headset 3 is connected to the computer 1 to be used by the computer user. The connector 4 has a recess in which the mobile unit 5 is placed in an upright position. Connector 4 establishes connections between its internal circuitry and an interface card 25 inserted in a slot formed in the housing of computer 1.

In Fig. 2, the notebook computer 1 includes a control circuit 10 to which the keyboard 2 of the computer 1 is connected, a voice processor 11, a packet processor 12 and a fax transceiver 13, all of which are connected to a USB (universal serial bus) interface 18. Voice processor 11 has a first analog input port for receiving a voice signal from the microphone 3A and converts it to a digital voice signal at a rate much lower than 64 kbps and a first digital output port from which the digital voice signal is delivered. In addition, the voice processor 11 has a second digital input port for receiving a lower-than-

1 64 kbps digital voice signal from the mobile unit 5 and converts it to an  
2 analog voice signal and a second analog output port from which the analog  
3 voice signal is delivered to the speaker 3B.

4 In response to command signals from the keyboard 2, the controller 10  
5 produces a number of control signals including an on/off control signal for  
6 providing a power-on-off control over the mobile unit 5, a voice recognition  
7 control signal for controlling the voice recognition circuit of the mobile unit, a  
8 mode control signal for operating the mobile unit in one of voice, packet and  
9 facsimile modes, and a dialing signal for placing a call in a manner as will be  
10 described. Further provided is a voice-to-text converter 14 connected to the  
11 microphone 3A for converting the voice input into character data, which is  
12 displayed via a video processor 16 on the screen of a display unit 17. A voice-  
13 input message for an electronic mail can be produced in this way and  
14 transmitted in packets from the packet processor 12.

15 A graphics data source 15 is provided to respond to an input from the  
16 keyboard 2 to produce a simulated image of the mobile unit on the computer  
17 screen in order that the user is given an impression that he is directly  
18 operating the mobile's keypad from the keyboard 2. All internal circuits of  
19 the computer 1 are supplied with a DC voltage from a rechargeable battery  
20 19, which also supplies its power to the mobile unit via the USB interface 18.  
21 Keyboard 2 supplies a command to the controller 10 for enabling the voice-to-  
22 text converter 14 and the graphics data source 15.

23 Interface card 25 is connected to the connector 4 via industry-  
24 standardized connector ports designated "a" through "j" and a grounded  
25 port not shown. Interface card 25 includes a USB interface 21 which is

1 coupled through a USB port 20 to the USB interface 18 of the computer 1.  
2 Battery power is supplied through the two power lines of the four-wire USB  
3 port 20 and all signals between the USB interfaces 18 and 21 are carried on the  
4 two signal lines of the USB port 20. The dotted lines in Fig. 2 indicate logical  
5 connections which will be established between the two USB interfaces under  
6 control of the controller 10 and phone controller 24.

7 A voltage sensor 22 and a battery charger 23 are provided. Voltage  
8 sensor 22 monitors the USB power lines to detect the voltage level of the  
9 rechargeable battery 19 and activates the battery charger 23 for charging the  
10 rechargeable battery of the mobile unit 5 when the computer's rechargeable  
11 battery 19 is charged at a level higher than a specified voltage.

12 A phone controller 24, provided in the interface card 25, is connected  
13 between the USB interface 21 and the connector 4. Phone controller 24  
14 receives an on-off control signal from the controller 10 for controlling the  
15 power switch of the mobile unit 5 and supplying serial command data to and  
16 receiving serial response data from the mobile unit 5. Electronic mail can be  
17 exchanged in serial data through the phone controller 24. The user can  
18 benefit from the large computer screen to prepare text messages for e-mail  
19 transmission and keep a record of transmitted e-mail messages in a hard disk  
20 of the computer.

21 The voice recognition control signal from the controller 10 is repeated  
22 by the phone controller 24 to the mobile unit 5 in order to receive a response  
23 signal (text data) indicating a phone number corresponding to an uttered  
24 subscriber name into the microphone 3A. A phone attachment/detachment  
25 signal is received from the connector 4, the signal being applied to the USB

1 interface 21 for activating the controller 10 when the mobile unit 5 is held in  
2 upright position on the connector 4.

3 In Fig. 3, the mobile unit 5 includes a controller 30 for providing  
4 interactive communication with the phone controller 24 by exchanging serial  
5 command and serial response signals. A voice processor 31 similar to the  
6 voice processor 11 is provided. A packet processor 32 and a fax transceiver  
7 33 are provided for communication with the packet processor 12 and fax  
8 transceiver 13. A phone attachment sensor 34 is provided in the connector 4  
9 to supply a phone attachment signal through connector port "i" to the  
10 interface card 25 in order to activate the controller 10 when the mobile unit is  
11 placed on the connector 4. When the mobile unit is removed from the  
12 connector 4, a phone detachment signal will be sent to the computer 1.

13 The mobile unit 5 has a rechargeable battery 35 that is charged with  
14 the DC voltage supplied from the rechargeable battery 19 of the computer.  
15 All internal circuits of the mobile unit 5 except for power saving circuitry are  
16 energized by the battery 35 via a power switch 36 which is controlled by an  
17 ON/Off control signal from the controller 30.

18 Switches 40 and 49 are provided to selectively establish paths or  
19 logical connections under control of the controller 30, as indicated by the  
20 dotted lines.

21 A wireless interface 48 is connected to the voice processor 31, packet  
22 processor 32 and fax transceiver 33 as well as to the memory 43 to receive a  
23 dialed phone number. Wireless interface 48 establishes a wireless  
24 communication link to the mobile network and initiates a call according to  
25 the phone number supplied from the memory 43. During an exclusively

1 mobile mode, the switch 40 connects the voice processor 31 to the  
2 microphone 42 and a speaker 47 and connects the packet processor 32 and fax  
3 transceiver 33 to the video processor 44 and the keypad 46.

4 Mobile unit 5 is provided with a voice recognition unit 41. When the  
5 mobile unit is not connected to the computer 1 and the voice recognition unit  
6 41 can be used for addressing the speed dialing memory 43 for a phone  
7 number corresponding to an input voice. In this case, the controller 30  
8 controls the switch 40 to establish a path 50 for coupling the microphone 42 to  
9 the voice recognition unit 41. The voice input from the microphone 42 is  
10 converted by the voice recognition unit 41 to text data, which is used by the  
11 memory 43 to make a search for a corresponding phone number, the phone  
12 number being displayed on the display panel 45 and used for initiating a call  
13 to the mobile network through a wireless interface 48. When a call is  
14 established, the controller 30 controls the switches 40 and 49 so that paths 51  
15 and 52 are established between the microphone 42 and speaker 47 on the one  
16 hand and the analog input and output ports of the voice processor 31 on the  
17 other, and paths 53 and 54 are established between the digital output and  
18 input ports of the voice processor 31 and the wireless interface 48.

19 Speed dialing memory 43 is connected to a video processor 44,  
20 through which phone numbers read out of the memory 43 can be displayed  
21 on a phone display panel 45. When the mobile unit is not attached to the  
22 computer 1, the phone display 45 provides a display of a phone number  
23 supplied from the speed dialing memory 43 and textual data generated by a  
24 keypad 46.

25 The following is a description of the operation of the computer 1 when



1 the mobile unit 5 is attached to the computer by way of the connector 4.

2 When the mobile unit 5 is held in position on the recess of connector 4,  
3 the phone attachment sensor 34 senses its presence and produces a phone  
4 attachment signal, which is sent through connector port "i" to the controller  
5 10 via USB interfaces 21 and 18. Note that all signals communicated between  
6 the USB interfaces 18 and 21 over the USB port 20 are in the form of packets.  
7 Controller 10 is enabled in response to the phone attachment signal so that it  
8 is ready for accepting command signals from the keyboard 2.

9 In response to a keyboard operation by the user, the controller 10  
10 produces a turn-on signal, which is sent through the phone controller 24 to  
11 the controller 30 of the mobile unit and turns on the switch 36. Mobile unit 5  
12 is activated to establish a wireless control channel to the mobile network. As  
13 long as the voltage of rechargeable battery 19 is higher than a specified level,  
14 the voltage sensor 22 will activate the battery charger 23 for charging the  
15 mobile's rechargeable battery 35 through connector port "j".

16 If the user desires to place a phone call using the mobile's speed  
17 dialing memory 43 and voice recognition unit 41 in a manner similar to that  
18 during the exclusive mobile mode, he sets the controller 10 through the  
19 keyboard 2 to produce a voice recognition control signal and a telephony  
20 (voice) mode signal, which are applied to the phone controller 24. Controller  
21 24 repeats the signals to the controller 30 via connector port "a". Controller  
22 30 operates the switches 40 and 49 to establish paths 55 and 56 for connecting  
23 the digital output of voice processor 11 which is applied through connector  
24 port "c" to the digital input of voice processor 31 and a path 57 (in switch 40)  
25 for connecting the analog output of the voice processor 31 to the voice

1 recognition unit 41. Simultaneously, the voice processor 11 is enabled by the  
2 controller 10.

3       The user then utters the name of a called party into the microphone  
4 3A. The voice signal from the microphone 3A is applied to the voice  
5 processor 11, where the voice input is converted to a low-rate digital speech  
6 signal and sent through connector port "c" to the voice processor 31. An  
7 analog voice output is generated by the voice processor 31 and applied  
8 through the path 57 to the voice recognition unit 41 and converted to text  
9 data, which is used by the memory 43 to make a search for a corresponding  
10 phone number. This phone number is sent from the controller 30 through  
11 connector port "b" to the phone controller 24, where it is delivered through a  
12 control bus 70 to the video processor 16 and displayed on the screen of the  
13 computer display 17. On the other hand, the same phone number is supplied  
14 on line 71 (Fig. 3) to the wireless interface 48 for initiating a call. When a call  
15 is established, the controller 30 controls the switches 40 and 49 so that paths  
16 58, 59 and 60 are established for connecting the digital output of voice  
17 processor 11 (which is received through connector port "c") to the digital  
18 input of the wireless interface 48 and connecting the digital output of wireless  
19 interface 48 to the digital input of voice processor 11 via connector port "d".

20       When the user activates the graphics data source 15 through keyboard  
21 2, an image 72 of the mobile unit 5 is displayed on the computer screen as  
22 shown in Fig. 4.

23       By operating a numeral key on the keyboard 2, the corresponding key  
24 is lit on the simulated mobile's image. At the same time, the entered numeral  
25 data is sent from the controller 10 to the phone controller 24 which repeats

1 the signal to the mobile controller 30. By repeating this process, the user can  
2 enter the address information of a called party and the controller 30 receives  
3 this address information and sends it to the wireless interface 48 through line  
4 71, which then establishes a communication link through the cellular mobile  
5 network.

6 When the user enables the voice-to-text converter 14 through the  
7 keyboard 2, a voice message can be entered through the microphone 3A to  
8 the voice-to-text converter 14, from which a text-converted data is supplied to  
9 the video processor 16 and displayed on the computer screen. An electronic  
10 mail can be formulated with such text data and transmitted to the mobile's  
11 controller 30 through USB interfaces 18, 21 and phone controller 24 to the  
12 connector port "a". In this way, the user is relieved of having to manipulate  
13 the mobile's small keys which are usually need to be operated repeatedly for  
14 entering a desired character.

15 Phone controller 24 allows phone numbers entered through the  
16 keyboard 2 to be transmitted as serial data through connector port "a" and  
17 stored into the speed dialing memory 43 of the mobile unit and allows e-mail  
18 messages to be displayed on the computer screen, instead of on the small-  
19 sized mobile's screen. Further, the phone controller 24 allows all operating  
20 status information of the mobile unit 5 to be received through serial data port  
21 "b" and put on display on the computer screen.

22 The user can specify from the keyboard 2 to the controller 10 as to  
23 which one of packet and facsimile modes is used to initiate a call. In response  
24 to such a keyboard input, the controller 10 produces a mode select signal  
25 (packet/fax) and enables one of the packet processor 12 or fax transceiver 13,

1 which is repeated by the phone controller 24 to the mobile's controller 30 via  
2 connector port "a". Controller 30, in response, establishes a two-way path in  
3 the switch 40 between one of the packet processor 12 and fax transceiver 13  
4 and a corresponding one of the packet processor 32 and fax transceiver 33.

5 If the call is in a telephony mode, the voice input to the microphone 3A  
6 is applied to the voice processor 11, where the signal is converted according  
7 to a predetermined coding algorithm to a lower-than-64-kbps digital voice  
8 signal and passed through the switches 40 and 49 to the wireless interface 48.  
9 This signal is translated to an uplink signal and transmitted to the mobile  
10 network. Digital voice signal from the network is carried on a downlink  
11 signal and received by the wireless interface 48, the digital voice signal being  
12 supplied via the switches 49 and 40 and connector ports "c" and "d" to the  
13 voice processor 11 where it is processed back to the original analog signal and  
14 applied to the speaker 3B.

15 If the mode select signal from the controller 10 indicates that the user  
16 wishes to send packets, the packet processor 12 is enabled by the controller 10  
17 to send packets to the mobile's packet processor 32 via connector port "e" for  
18 transmission to the mobile network. Packets from the network are first  
19 processed by the mobile's packet processor 32 and sent to the computer's  
20 packet processor 12 to be displayed on the computer screen. In a similar  
21 manner, the fax transceivers 13 and 33 are used for exchanging fax signals  
22 with remote stations.

23 It is seen that the user is relieved from the need to find a commercial  
24 AC outlet for charging the mobile unit 5 and from the need to use a power  
25 code for coupling the mobile unit to the AC outlet. Another advantage of the

1 present invention is that since the AC power supply is not necessary the  
2 mobile unit 5 no longer needs an AC-DC converter battery charger which  
3 adds an extra weight to the mobile unit.

4 With the combined use of a personal computer and a mobile unit, the  
5 user can access a wide range of multimedia applications on a simultaneous  
6 basis by utilizing the large screen size of the computer and the  
7 communication functions of the mobile unit such as video, voice and fax  
8 services.

9 Fig. 5 shows an alternative embodiment of the present invention. In  
10 this embodiment, the interface card 25 is located within the housing of the  
11 connector 4. In this case, the USB port 20 takes the form of a four-wire cable  
12 80 extending from the connector 4 to a USB port 81 of the computer 1.